

WFA-R Series



www.swedx.co.uk



HDMI, VGA, DVI,
HD-SDI Input



Lightweight



800 Nits
High Brightness



Magnetic
Module



Low Power
usage



Flexible
Install



5.8kg
Per Panel



Long
Lifespan



Features & Details

The WFA-R Series offers slim, lightweight indoor panels with magnetic modules, full front access, and flexible installation. High refresh rate and gray level ensure smooth, vivid image quality. Perfect for retail, corporate, and transport displays, WFA-R adapts to flat or curved walls. Its smart design enables wall-mount, hanging, or embedded installs with fast maintenance access.

| Model Number | WFA-R-1.9 | WFA-R-2.6 | WFA-R-2.9 | WFA-R-3.9 |
|---------------------------------|--|------------|------------|------------|
| Pixel Pitch(mm) | 1.95 | 2.604 | 2.976 | 3.91 |
| Module Size | 250 x 250 | 250 x 250 | 250 x 250 | 250 x 250 |
| Module Resolution(dot) | 128 x 128 | 96 x 96 | 84 x 84 | 64 x 64 |
| Module Assembly | 4 x 1 | 4 x 1 | 4 x 1 | 4 x 1 |
| Panel Size(mm) | 1000 x 250 | 1000 x 250 | 1000 x 250 | 1000 x 250 |
| Panel Resolution(dot) | 512 x 128 | 384 x 96 | 336 x 84 | 256 x 64 |
| LED Type | SMD1515 | SMD1515 | SMD1515 | SMD2020 |
| Brightness (cd/m ²) | | | | ≥800 |
| Support Input | Composite,S-Vido,Component,VGA,DVI,HDMI,HD_SDI | | | |
| Horizontal Viewing Angle | 160° | | | |
| Vertical Viewing Angle | 160° | | | |
| Gray Level | 16384 | | | |
| Refresh Rate | ≥3840Hz | | | |
| Max. AC power consumption | 650W/m ² | | | |
| Avg. AC power consumption | 200W/m ² | | | |
| Voltage | AC100~240 50/60HZ | | | |
| Operate Temp/Humidity | -20°C~+50°C,10~85% RH | | | |
| Operating Humidity | -30°C~+60°C,10~95% RH | | | |
| Protection grade | IP31 | | | |
| Environment | Indoor | | | |
| LED Lifetime(Hours) | 100,000 | | | |
| Weight(kg/pc) | 5.8 | | | |



Estimated Delivery Time - 25 Days

Model Numbers -

- SWX-DZ210-1
- SWX-DZ210-2
- SWX-DZ210-2.9
- SWX-DZ210-3