

Double Sided Floor Stand Outdoor LCD Digital Signage



www.swedx.co.uk

SWEDXUK



IP65
Certified



Protective
UV Film



5000 Nits
Sunlight Readable



Temperature &
Humidity Control



IK10
Rated



Vandal
Proof



PCAP Touch
(Optional)



Android
SOC (Optional)



Features & Details

Commercial grade ultra-high brightness panels 2500 - 5000nits, you can be rest assured that it will be readable in direct sunlight. Suitable for full outdoor integration, through tough weather with high and low temperatures, raining, snowing etc. The strong Aluminium housing and 6mm tempered glass covered kiosk makes the display vandal proof, it has also passed IP65 & IK10



Model Numbers -

- SWX-H13049
- SWX-H13055
- SWX-H13065
- SWX-H13075
- SWX-H13086
- SWX-H13043

Display	Panel Size	43"/49"/55"/65"/75"/86"
	Resolution	1920x1080 FHD/4K
	LCD Manufacturer	BOE/LG/AUO(Industrial grade panel, 105°C TNi heat resistant panel, wide working temperature-30~ +80°C)
	Viewing angle	89/89/89/89(L/R/U/D)
	Contrast ratio	1200:1
	Brightness	2500nits as standard (3500nits/4500nits can be customized)
	Aspect Ratio	16:9
	Active Area	1210(H) × 680(V) mm
	Operational Life Cycle- MTBF(hours)	50K hours
	Grey to Grey Response Time (ms)	6ms
Power	Input Voltage	AC110 - 240 ± 10%, 50 / 60 HZ
	Leakage Protection	30mA/0.1S
	Built-in Power Socket	1 pcs (EU/US/UK/AU/Swiss Standard optional, more sockets are optional)
	Timer Switch	1 pcs
	Max Power Consumption (w)	TBD

Estimated Delivery Time - 25 Days