

Double Sided Battery Powered Outdoor LCD Digital Signage

SWEDXUK

SWEDXUK

www.swedx.co.uk

SWEDXUK



IP65 Certified



Protective UV Film



2000 Nits Sunlight Readable



HDMI Input



Tempered Glass



14 Hour Charge & Battery Report



Battery Rechargeable



Android SOC (Optional)



Features & Details

Anti-Glare glass helps the screen to be easily readable in daylight and to provide better viewing angles for everyone. This glass is strong and vandal proof so should stop any unwanted damage. IP65 certification providing water proofing technology fit for the outdoors, created to face all types of climates.



Model Numbers -

- SWX-H11043-25

Display	Panel Size	43"
	Resolution	1920x1080 FHD/4K
	LCD Manufacturer	BOE/LG/AUO(Industrial grade panel, 105°C TNi heat resistant panel, wide working temperature-30~ +80°C)
	Viewing angle	89/89/89(L/R/U/D)
	Contrast ratio	1200:1
	Brightness	2500nits as standard (3500nits/4500nits can be customized)
	Aspect Ratio	16:9
	Active Area	1210(H) × 680(V) mm
	Operational Life Cycle-MTBF(hours)	50K hours
	Grey to Grey Response Time (ms)	6ms
	Power	Input Voltage
Leakage Protection		30mA/0.15
Built-in Power Socket		1 pcs (EU/US/UK/AU/Swiss Standard optional, more sockets are optional)
Timer Switch		1 pcs
Max Power Consumption (w)		TBD

Estimated Delivery Time - 25 Days