

## Foldable LED Poster



www.swedx.co.uk

SWEDX UK



Mobile App  
& Cloud Control



Foldable  
Design



800+ Nits  
High Brightness



Cascading  
Support



Rear  
Maintenance



Lightweight



Ultra-Thin  
Form Factor



Plug &  
Play



## Features & Details

The SWEDX Foldable LED Poster offers a lightweight, ultra-thin design with plug-and-play setup and cloud control. Its dual or single-sided display, foldable frame, and vibrant 3840Hz visuals make it ideal for high-impact indoor environments. Perfect for retail stores, exhibitions, events, and airports, this portable digital signage solution delivers eye-catching content in seconds. Its foldable design ensures easy transport and fast deployment in tight or mobile spaces.



FOLDABLE LED Poster			
Model No	P1.5	P1.8	P2.5
Pixel Pitch	1.538mm	1.86mm	2.5mm
LED Type	SMD1212	SMD1515	SMD2020
Module Resolution	208x104	172x86	128x64
Screen Resolution (pixels) (each side, folded)	416x1248	344x1032	256x768
Screen Resolution (pixels) (unfolded)	832x1248	688x1032	512x768
Total Pixel (dots) (each side, folded)	519,168	355,008	196,608
Total Pixel (dots) (unfolded)	1,038,336	710,016	393,216
Driving Mode	1/52	1/43	1/32
Minimum Viewing Distance	≥ 1.9m	≥ 2.2m	≥ 3.1m
Brightness (nits)	600-800	650-800	650-800
Module Size	320mm x 160mm		
Cabinet Size	640mm x 1920mm folded / 1280 x 1920 unfolded		
Screen Size	640mm x 1920mm folded / 1280 x 1920 unfolded		
IP Grade	Indoor IP31		
Refresh Rate	≥ 3840Hz		
Color processing (Bit)	13bits - 16bits		
Viewing Angle (H/V)	160°/160°		
Maximum Power Consumption	≤ 1200W/unit		
Average Power Consumption	≤ 400W/unit		
Input Voltage	AC 110V / 220 V @ 50Hz/60Hz		
Operating Temperature	-20°C - 60°C		
Operating Humidity	10% - 90%		
Cabinet Material	Aluminum profile		
Maintenance Method	Rear Service		

### Model Numbers -

- SWX-DZ250-1.5
- SWX-DZ250-1.8
- SWX-DZ250-2.5

Estimated Delivery Time - 25 Days