Wall Mount Outdoor LCD Digital Signage

- IP65 Certified
- Protective UV Film
- 2500 Nits Sunlight Readable
- Temperature & Humidity Control
- IK10 Rated
- Vandal Proof
- PCAP Touch (Optional)
- Android SOC (Optional)

Features & Details

The fully enclosed design allows for 24/7 outdoor usage. IP65 Rated perfect for all typed of harsh weather. The 6mm Tempered glass also makes it vandal proof as it also has an IK10 Rating.
When the internal working temperature reach 65°C, LCD backlight will shutdown automatically to prevent the machine from overheating. LCD backlight turns on again when internal temps reach 53°C - These variables can be changed.

Display	Panel Size	43"/49"/55"/65"/75"
	Resolution	1920×1080 FHD/4K
	LCD Manufacturer	BOE/LG/AUO(Industrial grade panel, 105℃ TNI heat resistant panel, wide working temperature-30~ +80℃)
	Viewing angle	89/89/89/89(L/R/U/D)
	Contrast ratio	1200:1
	Brightness	2500nits as standard (3500nits/4500nits can be customized)
	Aspect Ratio	16:9
	Active Area	1210(H) × 680(V) mm
	Operational Life Cycle-MTBF(hours)	50K hours
	Grey to Grey Response Time (ms)	6ms
Power	Input Voltage	AC110 ~ 240 ± 10%, 50 / 60 HZ
	Leakage Protection	30mA/0.1S
	Built-in Power Socket	1 pcs (EU/US/UK/AU/Swiss Standard optional, more sockets are optional)
	Timer Switch	1 pcs
	Max Power Consumption (w)	TBD

Model Numbers -

- SWX-H14043
- SWX-H14049
- SWX-H14055
- SWX-H14065
- SWX-H14075
- SWX-H14086

Estimated Delivery Time - **25 Days**