

Pro Plus Panel Series



www.swedx.co.uk



Cold Screen



4H Hardness, Moisture-Proof, Wipeable



1000 Nits High Brightness



High Contrast Ratio




Long Term Black Uniformity



Crystal Clear & Smooth Image



Flip Chip Mini LED



Patented 3-In-1 Board



Features & Details

This LED display solution offers pixel pitches of P1.25, P1.56, and P1.87, with 1000nit brightness and an ultra-smooth 7680Hz refresh rate. It guarantees flawless, flicker-free visuals—ideal for high-speed filming and dynamic virtual production. Built on advanced flip chip mini LED and patented 3-in-1 board technology, it provides long-term black uniformity, matte surface finish, high contrast, and low power consumption. The larger 300×168.75mm module ensures seamless visual integration for premium AV environments.



PRO PLUS PANEL SERIES: SPECIFICATIONS			
Pixel Pitch	1.25	1.56	1.87
Module Size (mm)	150 * 168.75 mm		
Module Resolution	120 * 135	96 * 108	80 * 90
Surface	Matte Surface		
Cabinet Size (mm)	600 * 337.5 * 39.75		
Cabinet Weight (kg)	4		
Resolution	480 * 270	384 * 216	320 * 180
Flash Memory	Supported		
Brightness (nit)	1,000 (after calibration)		
Refresh Rate (Hz)	7680		
Greyscale (bit)	15		
Contrast Ratio	15,000 : 1		
Colour Temperature (K)	9300 (standard)		
View Angle (°)	160		
Input Voltage	AC 100~240V, 50/60Hz		
Peak Power (W/m ²)	495	495	450

Estimated Delivery Time - 25 Days

Model Numbers -

- SWX-C15012
- SWX-C15015
- SWX-C15018