

# UTM Series - LED Display Outdoor



IP67  
Certified



2-In-1 Power  
& Signal Cable



5000 Nits  
High Brightness



Easily  
Serviceable



Advanced  
Protection



1.65kg  
Per Panel



37mm  
Thick



Wide Viewing  
Angles



## Features & Details

The UTM Series is built for lightweight, plug-and-play outdoor use. Its compact design and smart 2-in-1 cabling make setup fast and easy. Perfect for harsh environments and creative installs where space and weatherproofing are critical, UTM panels combine ease of use with powerful performance.



Title	UTM2	UTM4
Pixel Pitch	2.85 mm	4 mm
LED Configuration	SMD1415 LED	SMD1921 LED
Panel Dimension:	320mm x320mm x 37 mm	320mm x320mm x 37 mm
Panel Resolution	112 x 112	80 x 80
Weight Per Panel	1.65 kg   3.6 lb	1.65 kg   3.6 lb
Power Max/Average	680W/300W	680W/300W
BTU Max/Average	2310/1000	2310/1000
Serviceability	Front / Rear	Front / Rear
Brightness	4500nits	5000nits
Gray Scale	14 bit	14 bit
Refresh Rate	3840 Hz	3840 Hz
Scan Ratio	1/23	1/16
Viewing Angle	140°/140° (H/V)	140°/140° (H/V)
IP Rating	IP67	IP67
Operating Environment	Out door	Out door

Estimated Delivery Time - 25 Days

### Model Numbers -

- SWX-DZ150-2
- SWX-DZ150-4