

SWX-D Series Display



www.swedx.co.uk

SWEDXUK



LCD Technology



Lightweight Design



Automatic Brightness Adjustment



Multiple Connectivity Ports



Intelligent temperature Control



Ultra Thin



Rotation Support



Hanging/Floor Standing Options



Features & Details

The D-Series double-sided display and Q43 high-contrast display deliver exceptional brightness, vivid colours, and flexible installation options for impactful commercial advertising in any environment. Designed for 24/7 operation, these displays feature intelligent temperature control, automatic brightness adjustment, and versatile connectivity to ensure reliable, high-quality performance across various retail, corporate, and public spaces.



FUNCTIONAL PARAMETER			
	Standalone Version		Android Version
System			Android7.1/8.1/11.0
RAM			2G (Expandable to 4G)
Memory	8G		8G (Expandable to 32G)
WiFi	No		Yes
Video Format	PG, MPG-1, MPG-2, MPG-4, AVI, Mp4, Pm3, TS, MKV, WMV		PG, MPG-1, MPG-2, MPG-4, AVI, Mp4, Pm3, TS, MKV, WMV
Audio Format	Mp3, 24bit linear PCM7.1		Mp3, 24bit linear PCM7.1
Picture Format	GIF, JPEG, PNG, BMP		GIF, JPEG, PNG, BMP
Interface	USB, TF Card		RJ45, USB, HDMI
SCREEN PARAMETER			
Panel Brand	LG/AUO/BOE	Screen Type	IPS (LCD Backlight)
Display Ratio	16:9	Max Resolution	1920*1080P
Brightness	250-400CD/M ²	Contrast Ratio	1000:1
Visual Angle	89/89/89/89(L/R/U/D)	Color	16.7M
Stabdard Size	15.6/18.5/21.5/24/27/32 Inch or customized		
SCREEN PARAMETER			
Operating Temperature	0°C~50°C	Storage Temperature	-10°C~60°C
Working Humidity	5%~90%	Storage Humidity	5%~100%
Input Voltage	DC 12V-5A		

Estimated Delivery Time - 25 Days

Model Numbers -

• SWX-K120