

IP66 Wall Mount Outdoor LCD Digital Signage



www.swedx.co.uk

SWEDX UK



IP66
Certified



Protective
UV Film



4000 Nits
Sunlight Readable



Temperature &
Humidity Control



IK10
Rated



Vandal
Proof



PCAP Touch
(Optional)



Android
SOC (Optional)



Features & Details

Smart monitoring panel prevents the LCD display from overheating. If the display temp reaches 25oc the fans start spinning, increased temps means increased fan rpm. 26mm per single bezel. Combining with more screens helps create a more seamless one screen look. And can help create a stunning looking menu board for example.



LCD Display	Panel	32" 43" 49" 55" 65" 75" LCD panel
	Resolution	1920*1080
	Display mode	Normally full black
	Contrast ratio	1400:1
	Viewing angle	89/89/89/89 (L/R/U/D)
	Brightness	3000cd/m ² or 4000cd/m ²
	Aspect Ratio	9: 16
Android Operating System(Option 1)	CPU	RK3399, Dual core Cortex-A72 + Quad core Cortex-A53, MAX 1.8GHz
	GPU	ARM Mali-T864
	RAM	4GB
	Internal memory	64GB EMMC
	Operation system	Android 11
	Interface	HDMI Output
	Ethernet Port	1
	USB Port	2
	AC Power Port	1

Model Numbers -

- SWX-H16032
- SWX-H16043
- SWX-H16049
- SWX-H16055
- SWX-H16065
- SWX-H16075

Estimated Delivery Time - 25 Days