

Outdoor Self Order Kiosk Floor Stand/Wall Mount



www.swedx.co.uk

SWEDX UK



IP65 Certified



Protective UV Film



2500 Nits Sunlight Readable



Temperature & Humidity Control



IK10 Rated



Vandal Proof



Card Reader



Android SOC (Optional)



Features & Details

Thanks to their commercial grade ultra-high brightness panels, these displays are up to 10 times brighter than a domestic TV and are easily readable even in direct sunlight. When the internal working temperature reach 65°C, LCD backlight will shutdown automatically to prevent the machine from overheating. LCD backlight turns on again when internal temps reach 53°C - These variables can be changed.



Display	Panel Size	32"
	Resolution	1920x1080 FHD
	LCD Manufacturer	BOE/LG(Industrial grade panel, high TNi heat resistant panel, wide working temperature-30~ +80°C)
	Viewing angle	89/89/89/89(L/R/U/D)
	Contrast ratio	1200:1
	Brightness	2500nits sunlight readable
	Aspect Ratio	16:9
	Active Area	940*530mm
	Operational Life Cycle-MTBF(hours)	50K hours
	Grey to Grey Response Time (ms)	6ms
	Power	Input Voltage
Leakage Protection		30mA/0.1S
Built-in Power Socket		1 pcs (EU/US/UK/AU/Swiss Standard optional, more sockets are optional)
Timer Switch		1 pcs
Max Power Consumption (w)		200W

Model Numbers -

- SWX-H15032

Estimated Delivery Time - 25 Days